

## PRODUCT AJBAS Runner.

## **Product Description:**

A jbas runner fabricated from cold rolled galvanized steel are used at the floor and soffit to support the wall studs.

Ajbas's runner features knurledfaces which is the pattern of small ridges formed on the track to prevent

screws from slipping and damaging the board, without compromising the strength or thickness of the steel.

# Field of Application:

A pplicable for Shaft Wall Partition, Fire rated Stud ceiling system at Staircase, lift shafts and other such applications.

## Advantages:

- Good fire protection.
- Good sound insulation.
- Environment friendly.
- Easy & fast installation.
- Light weight co
  Safe when following safety instructions.

## Material Storage & Handling Conditions:

- Products are supplied in pack and sub-pack quantities and should be handled in accordance with the recommendations contained in AS 1470 – Health and Safety at Work Principles and Practice.
- Where mechanical lifting or moving equipment is required, trained andlicensed operators are to be used.
- Metal products should be stored in an environmentally-friendly area away from airborne contaminants such as acid and salt sprays.
- People with sensitive skin conditions should seek medical advice before prolonged handling of metal products; hands should be washed before eating and for personal hygiene.
- Non-fogging goggles (AS/NZS 1336) should be worn when cutting metal sections.

## Cold-Formed Steel Design References:

- North American Specification for the Design of Cold-Formed Steel Structural Members (AISI S100, AISIS200).
- Analysis and Design of Cold Formed Members is according to LRFD & ASD Method.
- Cold-Formed Steel Design, Fourth Edition by Wei-Wen Yu & Roger A. LaBoube .

#### **Product Characteristics**

Technical Parameters	Detail
Coating	Z 70, Z 90, Z 120, Z 180 & Z 275
Yield Strength	240 MPA - 310 MPA
Tensile Strength	340 MPA - 420 MPA
Material	Galvanized Steel
Flanges (mm)	5 / 10 MM
Length	Standard 3 meters and can be produced on request.
Thicknees (mm), (TCT)	0.35,0.38,0.40,0.45 0.50,0.60,0.80
Sizes (mm) , (Depth)	41, 48 ,75 & 100





